

NOV 28 2007

Docket No. F-8866

Scr. No. 10/554,037

AMENDMENTS TO THE SPECIFICATION:

Please amend the indicated paragraphs of the specification in accordance with the amendments indicated below.

Page 10, sixth full paragraph:

As shown in FIG. 1-FIG. 7, the power generating system 1 is comprising a power generator 2 electrically generating DC power, an inverter circuit 3 for converting DC power generated by the power generator 2 into AC power to output to a ~~[[the]]~~ single phase AC system, a switching mechanism Sm to switch the DC power voltage of the power generator 2 in multi-levels, a control device 4 controlling ~~[[these]]~~ the switch mechanism Sm and switching elements 51-54 of the inverter circuit 3, and a voltage detector 5 applying input to ~~[[enter]]~~ the control device 4 after detecting the single phase AC system voltage.

Page 18, first full paragraph:

Then, when the voltage of the single phase AC system changes from negative to positive, the switching elements 51 and 54 are conducted and the switching elements 53 and 52 are turned off, whereas when the voltage of the single phase AC system changes from positive to negative, the switching elements ~~[[53]]~~ 52 and 53 are made conductive and the switching elements 51 and 54 are turned off.

Docket No. F-8866 .

Ser. No. 10/554,037

Page 21, fourth full paragraph:

The power generating system 1 is composed of a box-shaped main body case 80 made from synthetic resin with excellent durability, a lid member 81 made from synthetic resin covering the upper part of the main body case 80, a solar battery substrate 82 stored in the main body ~~case 81~~ case 80, an electronic component substrate 83, a plurality of electric double layer capacitors 29a and 29b and an inverter circuit 3.

Page 33, abstract:

ABSTRACT OF THE DISCLOSURE

A power generating system ~~comprises~~ includes a power generator [[2]] generating DC power, and an inverter circuit [[3]] for converting DC power into AC power [[: the]]. The power generator ~~comprises~~ has a plurality of power generating modules [[21-28]] each ~~comprising~~ including a plurality of power generating units [[30]] and at least one electric storage [[means]] device connected to each of the plurality of power generating modules [[21-28]]. A plurality of first switch ~~means~~ S11a-17a devices connect/disconnect each of [[the]] positive electrodes [[62]] of the plurality of power generating modules [[22-28]] to/from a positive bus [[6]], a plurality of second switch ~~means~~ S11b-17b devices connect/disconnect each of the positive electrodes [[62]] of the plurality of power generating modules [[22-28]] to/from [[the]] negative electrodes [[60]] of the power generating modules [[21-27]]

Docket No. F-8866

Ser. No. 10/554,037

which are contiguous to [[the]] one side, a plurality of third switch means ~~S1-S7~~
devices connect/disconnect each of the negative electrodes ~~60 of the plurality of~~
~~power generating modules 21-27~~ to/from a negative bus [[7]], and the DC output
voltage can be increased/decreased stepwise by switching the switch devices means
~~S1-S7, S11a-17a and S11b-S17b.~~

A cleanly type version of the abstract is provided on the following separate
page.